

## SPECIFICATIONS FOR DOUBLE BOILERLESS ELECTRIC COMBI OVEN

Oven shall be model **BX-142E** as manufactured by the Combi Division of Blodgett Oven Corporation. Combi-Oven/Steamer shall have all the following standard and accessory features:

### EXTERIOR CONSTRUCTION

- Stainless steel top, front and sides
- Dual pane tempered viewing window with hinged inner glass for easy cleaning
- Door mounted condensate trough
- Top and bottom mount, easily adjustable door hinges
- Pivot out user interface panel for service access

### INTERIOR CONSTRUCTION

- Fully welded stainless steel frame
- Fully insulated cooking chamber
- Fixed drain bottom center of cavity
- Easily removable stainless steel side rails
- 316 stainless steel coved corner liner for ease of cleaning

### OPERATION

- Standard control with function selection for steam, combi, hot air, and cool down
- Retherm band on control
- Steam on demand feature
- Thermostat control to 500F
- Multiple speed reversing fan for even bake
- Dual stage door latch to vent steam before fully opening door
- Cavity vent control provides ability to release steam at the turn of a switch
- Integral door switch
- Open vented system. Condenses steam and drains away by-products of the cooking process, eliminates flavor transfer

### CAPACITY

- Fourteen 12" x 20" x 2-1/2" deep pans at 3-1/4" spacing
- Seven 18" x 26" deep pans at 3-1/4" spacing

### STANDARD FEATURES

- Five (5) stainless steel wire shelves per section (capacity for 7)
- Hinged pressure panel for cleanability
- Four halogen lights for superior cavity illumination
- Retractable hose reel hidden behind door, no extraneous hoses
- Stacking kit and casters for double stack ovens
- Pressure spray bottle for oven cleaning
- 6-1/2" core temperature probe
- Start-up inspection service by factory authorized service agent
- One year parts and labor oven warranty\*

### REQUIRED ACCESSORIES

- ACS-22-8 22" high stand with universal pan slides

### OPTIONAL ACCESSORIES

- Limited Extended Warranty (one extra year maximum, for total of 2 years.)
- Blodgett – Combi Fry Pan
- Extra oven racks

- Legs (recommended for ease of leveling for uneven floors)
- SMFS2 Terry Water Treatment System for Scale & Corrosion Control-One Per Section

- ELIGIBLE BIDDER MUST VISIT JOB SITE.
- ALTERNATES NEED TO BE SUBMITTED FOR APPROVAL 10 DAYS PRIOR TO BID OPENING.
- SUCCESSFUL BIDDER TO DELIVER, UNCRATE, SET IN PLACE, LEVEL, AND REMOVE CRATING.
- FINAL CONNECTIONS BY OTHERS
- BIDDER WILL HONOR PRICES FOR A PERIOD OF ONE YEAR FROM THE BID DATE\_\_\_\_\_yes\_\_\_\_\_no.
- BIDDER WILL HONOR PRICING FOR COOPERATIVE PRICING\_\_\_\_\_yes\_\_\_\_\_no.

(Additional travel/mileage charges may apply to systems that are located outside the bidding system's area)