

SPECIFICATIONS FOR SINGLE ELECTRIC COMBI OVEN

Oven shall be model **BCX-14E** as manufactured by the Combi Division of Blodgett Oven Corporation. Combi-Oven/Steamer shall have all the following standard and accessory features:

EXTERIOR CONSTRUCTION

Stainless steel top, front, sides and right hand door hinge
Dual pane tempered viewing window with hinged inner glass for easy cleaning
Door mounted condensate trough
Top and bottom mount, easily adjustable door hinges
Pivot out user interface for service access

INTERIOR CONSTRUCTION

Fully welded stainless steel frame
Fully insulated cooking chamber
Fixed drain bottom center of cavity
Easily removable stainless steel side rails
Coved corner liner for ease of cleaning

OPERATION

Standard control with function selection for steam, combi, hot air, cool down, Vario Steam® and steam on demand feature
Thermostat control with range of 150-500°F (66-260°C)
Four speed reversing fan for even bake
Dual stage door latch to vent steam before fully opening door with integral door switch
Open vented system. Condenses steam and drains away by-products of the cooking process, eliminates flavor transfer
Self contained, self-flushing steam generator separate from cooking compartment for instant steam recovery when switching modes
Control prompts user to delime when steam generator requires deliming
Voltage required:_____

CAPACITY

Fourteen 12" x 20" x 2-1/2" deep pans at 3-1/4" spacing – per section
Seven 18" x 26" deep pans at 3-1/4" spacing – per section

STANDARD FEATURES

Five (5) stainless steel wire shelves per section (capacity for 7)
Hinged pressure panel for clean-ability
Four halogen light for superior cavity illumination
Retractable hose reel hidden behind door, no extraneous hoses
Pressure spray bottle for oven cleaning
Stacking kit and casters for double stack ovens
Semi-auto delime system with deliming bottle and pump assembly
Pressure spray bottle for oven cleaning
6-1/2" Temperature probe
Start-up inspection service by factory authorized service agent
One year parts and labor oven warranty

REQUIRED ACCESSORIES

ACS-22-8 22" high stand with universal pan slides

OPTIONAL ACCESSORIES

Limited Extended Warranty (one extra year maximum, for total of 2 years.)
Blodgett – Combi Fry Pan
Extra oven racks
SMFS2 Terry Water Treatment System for Scale & Corrosion Control

- ELIGIBLE BIDDER MUST VISIT JOB SITE.
- ALTERNATES NEED TO BE SUBMITTED FOR APPROVAL 10 DAYS PRIOR TO BID OPENING.
- SUCCESSFUL BIDDER TO DELIVER, UNCRATE, SET IN PLACE, LEVEL, AND REMOVE CRATING.
- FINAL CONNECTIONS BY OTHERS
- BIDDER WILL HONOR PRICES FOR A PERIOD OF ONE YEAR FROM THE BID DATE_____yes_____no.
- BIDDER WILL HONOR PRICING FOR COOPERATIVE PRICING_____yes_____no.
(Additional travel/mileage charges may apply to systems that are located outside the bidding system's area)