

WASHDOWN SYSTEM - WALLMOUNT SPECIFICATIONS

Commercial Washdown System- Shall be **Model 600-WDF, Food Service Package** as manufactured by **SMT**. Unit shall have all standard features of **SMT** and the following:

- 2.2 GPM @ 1100 PSI, 115V
- 2 H.P. motor
- Adjustable chemical selector with flush feature
- Pressure gauge, 2000 PSI, Liquid filled
- 36" spray gun / wand assembly with dual nozzle
- S/S cover and frame
- 3 cylinder CAT super flow plunger pump
- 6' water inlet supply hose
- Anti-backflow protection / Float tank
- S/S wall mount brackets with gun holder
- 4' Cord with GFCI
- Sanitizer chemical selector with flush feature and additional chemical basket
- SMT-200-RW manual rewind hose reel
- Thermal limit switch
- ETL-CSA Listed
- (2) Chemical basket
- 75' high pressure hose
- Maintenance Kit: Water filter assembly with one 5 micron filter, 6' supply hose, replacement filter and hydraulic pump oil
- Trap shooter spray gun with flexible wand that cleans grease traps and drains, with 10' hose
- Hummer Jet Jr.
- Wall & Tile Brush

Accessory:

- Additional 50' High Pressure Hose
- Quick connects for additional Hose
- Portable Hose Reel
- ELIGIBLE BIDDER MUST VISIT JOB SITE.
- ALTERNATES NEED TO BE SUBMITTED FOR APPROVAL 10 DAYS PRIOR TO BID OPENING.
- SUCCESSFUL BIDDER TO DELIVER, UNCRATE, SET IN PLACE, LEVEL, AND REMOVE CRATING.
- FINAL CONNECTIONS BY OTHERS
- BIDDER WILL HONOR PRICES FOR A PERIOD OF ONE YEAR FROM THE BID
DATE____yes____no.
- BIDDER WILL HONOR PRICING FOR COOPERATIVE PRICING____yes____no.
(Additional travel/mileage charges may apply to systems that are located outside the bidding system's area)