

SPECIFICATION FOR 40 GALLON ELECTRIC TILT SKILLET (BRAISING PAN)

Tilt Skillet shall be model BLG-40E as manufacturer by Blodgett. The kettle shall have the following standard and accessory features:

CONSTRUCTION

- #4 finish 10 gauge stainless steel pan with polished interior
- One piece coved corner stainless steel pan with angled front for easy pour
- Narrow footprint
- 5/8" thick stainless steel clad plate
- Permanent lubricated, self-contained gear box tilt mechanism
- Welded stainless steel tubular legs with bullet feet on front legs and flanged adjustable feet on back legs, all adjustable

OPERATION

- Integrally mounted controls
- Power switch
- Thermostat with OFF position
- Thermostat indicator light
- High temperature cut-off
- 160-445°F (71-230°C) temperature range

STANDARD FEATURES

- Spring assist hinged stainless steel cover with handle
- No drip condensate guide
- Removable pour strainer
- Manual tilt action
- Voltage to be determined\_\_\_\_\_
- One year parts and labor warranty\*

OPTIONS AND ACCESSORIES

- Single pantry faucet with swing spout
- Double pantry faucet with swing spout
- Etched markings/Gallons
- 2" (50mm) draw off valve
- 3" (76mm) draw off valve
- Pan carrier (40 gallon only)
- Steam pan insert

- ELIGIBLE BIDDER MUST VISIT JOB SITE.
- ALTERNATES NEED TO BE SUBMITTED FOR APPROVAL 10 DAYS PRIOR TO BID OPENING.
- SUCCESSFUL BIDDER TO DELIVER, UNCRATE, SET IN PLACE, LEVEL, AND REMOVE CRATING.
- FINAL CONNECTIONS BY OTHERS
- BIDDER WILL HONOR PRICES FOR A PERIOD OF ONE YEAR FROM THE BID DATE\_\_\_\_yes\_\_\_\_no.
- BIDDER WILL HONOR PRICING FOR COOPERATIVE PRICING\_\_\_\_yes\_\_\_\_no.  
(Additional travel/mileage charges may apply to systems that are located outside the bidding system's area)